X2™

This online-capable controller features rapid schedule programming and advanced water-saving features.

KEY BENEFITS

- Number of stations:
  - 4, 6, 8, or 14 (fixed models)
- Wi-Fi capable controller automatically managed by Hydrawise® software
- Backlit display provides optimal visibility in any light
- 3 flexible programs with 4 start times each and up to 6-hour run times
- QuickCheck™ provides simple diagnostics of faulty field wiring
- Hide Programs option shows 1 program and 1 start time for simplification
- Suspend irrigation up to 99 days during the off-season
- Short-circuit protection detects wiring faults and skips the station without system damage
- Easy Retrieve™ memory backups the full irrigation schedule
- Delay Between Stations for slow-closing valves or pump recharge
- Cycle and Soak prevents water waste and runoff in areas with elevation changes or tight soils
- Seasonal adjustment for quicker schedule adjustments without changing run times

WI-FI MODULE BENEFITS

- Provides rapid programming, online irrigation management, and controller status alerts
- Standard ABC programming with 3 programs and 6 start times, and run times up to 24 hours
- Predictive Watering™ provides precise weather adjustments for maximum water savings
- Compatibility with Amazon Alexa™ and Control4® home automation
- See complete WAND Wi-Fi module benefits and specifications on **page 111**

OPERATING SPECIFICATIONS

- Transformer input: 120 VAC or 230 VAC
- Transformer output (24 VAC): 1 A
- Station output (24 VAC): 0.56 A
- P/MV output (24 VAC): 0.28 A
- Sensor inputs: 1
- Approvals (controller): Plastic IP44, UL, cUL, FCC, CE, RCM
- Approvals (module): Wi-Fi b/g/n, Bluetooth 5.0, CE, UL, RCM, FCC
- Warranty period: 2 years

X2 - SPECIFICATION BUILDER: ORDER 1 + 2 + 3

1 Model	2 Transformer	3 Plug
X2-4 = 4-station	**00** = 120 VAC	**(blank)** = American plug
X2-6 = 6-station	**01** = 230 VAC	**E** = European plug
X2-8 = 8-station		**A** = Australian plug
X2-14 = 14-station		

Examples:
X2-1401-E = 14-station controller, 230 VAC internal transformer with European plug
X2-1401-A = 14-station controller, 230 VAC internal transformer with Australian plug

WAND WI-FI MODULE

Model	Description
WAND	Wi-Fi module for Hydrawise water management software



X2
Height: 23 cm
Width: 19 cm
Depth: 10 cm



WAND Wi-Fi Module
Height: 2 cm
Width: 5 cm
Depth: 5 cm

Compatible with:

Hydrawise® Software
Page 108

Rain-Clik Sensor
Page 144

ROAM Remote
Page 137
ROAM XL Remote
Page 138

Smart WaterMark
Recognised as a responsible water-saving tool when used with the WAND Wi-Fi module

Amazon Alexa is a trademark of Amazon.com Inc. or its affiliates. Control4 is a registered trademark of Control4 Corporation in the United States and/or other countries.